



ESA Euro Profil

ESA501 PREMIUM



Premium escutcheon

Can be used for many European mortise locks. For wooden, steel or tubular frame doors. The main electronics are outside, the security-relevant electronics are inside. Outer door handle rotates freely, inner door handle always engaged. Memory capacity for up to 99 PIN codes. LED for status display.

The advantages at a glance

- Can be used with many European mortise locks
- Can be used with standard or narrow profile doors
- For use in indoor areas
- Door leaf between 40 and 100 mm thick, in 5 mm increments
- Can be used with a backset of 25 mm or more
- Outside door handle rotates freely
- Inside door handle always engaged
- Main electronics on outside
- Security-relevant electronics inside
- Battery inside
- Coupling inside
- Mechanical cylinder (optional)
- Existing cylinder can continue to be used
- Handle spindle easily replaced
- Fastened with three bolts
- LED for status display (red/green/orange)

Scope of delivery

- 1 escutcheon with battery (Lithium CR123A) and installation instructions
- Screws and drilling template

Technical attributes	
PINpad	PIN code - 4 up to 6 digits
Approvals	CE, EN179, EN1906, DIN18273
Dimensions	312 x 41 x 10/20 mm (H x W x D)
Version	Premium = Higher security version up to grade 3 (EN 1906) with approvals on fire (DIN18273), escape (EN179) route and security
Handle	U-Shape
Surface	Stainless steel brushed (ST)
Distance (others on request)	Distance 72 mm, 92 mm; Spindle 9 mm
Door leaf thickness	Door leaf between 40 and 100 mm thick, in 5 mm increments
Backset	> 25 mm
Battery	1 x Lithium CR123A
Battery life	> 40,000 cycles (for max. 3 years)
Protection rating	IP 54
Operating temperature range	-25 °C to +60 °C
Humidity	< 85 % (condensation-free)
Status	LED (red/green/orange)

Distance	
72 mm	0
92 mm	1

Door leaf thickness	
40-45 mm	K
45-50 mm	L
50-55 mm	M
55-60 mm	N
60-65 mm	O
65-70 mm	P
70-75 mm	Q
75-80 mm	R
80-85 mm	S
85-90 mm	T
90-95 mm	U
95-100 mm	V

Article / Feature	
ESA501 PREMIUM	5 0 1 1 1 0 - 9 * 1 * 2 1 1 -

