


ABLOY® FD461

Mechanical double door coordinator

Product description ABLOY FD461 is a stylish and compact fire door closing system. It is suitable for double doors that are normally closed. Coordinator is placed inside the sliding rail which guarantees a durable protection against vandalism. Recommended to be used with ABLOY DC250 door closers (2 pcs).

- Overview of Advantages
 CE certified according to EN1158
- Maximum door leaf weight 120 kg and hinge distance 2800 mm
 Installed with door closer that can be adjusted to force size EN 3-6
 If installating on non-hinge side, then must use accessory set FD120
 Active door will not close before inactive door has closed

- If installating on hinge side, then must use carry bar FD101
 If installating on non-hinge side, then must use carry bar FD102



Technical data


| Technical data | |
|--|--|
| Door leaf width up to | 1400 mm |
| Hinge side frame installation: | |
| Hinge distance | 1250-2800 mm |
| Minimum passive door width | 350 mm |
| Active/passive door max. opening angle | 180° (With DC240 only) |
| Non-hinge side frame installation: | |
| Hinge distance | 1400-2800 mm |
| Minimum passive door width | 350 mm |
| Active door max. opening angle | 105° |
| Passive door max. opening angle | 115° |
| Door swing directions | Left/right handed |
| Weight | 2,6 kg |
| Certified in compliance with | EC-Certificate of conformity 0432-CPD-0049 |
| CE marking for building products | Yes |
| Basic colours | White (RAL 9016), Silver (EV1), Painted brass, Brown (RAL 8014), Black (RAL 9005), Customised finish |
| Optional cover | Stainless steel |
| Certified door closers | DC250, DC330, DC240 (hinge side only) |

We reserve the right to make alterations to the products described in this leaflet.



ABLOY[®] FD461 Mechanical double door coordinator

Accessories



Opening damper FD115



Installation

