# Planet MinE-S (s = Soundproof)

30 x 40 mm / 13 x 30 mm | ↓ 27 mm | ← 27 dB
























### Main features

- Especially for passive building and low energy houses
- Closed rooms with Ventilation systems / toilet / bathroom
- Air circulation / air equalization
- Seal height up to **J 27 mm**
- Sound absorption on seam < 27 dB at an air-gap of 7 mm
- Sound absorption at simultaneous air passage
- Air passage 200 m³/h
- Reading 30 m³/h at a pressure difference of 3,9 Pa (door width 1050 mm)
- Soft sililcone bevel lip seal
- Compensation of 15 mm in case of sloping floor at door width of 1000 mm
- Automatic compensation at inclined / uneven floors
- No extra need to cut off silicone at both ends
- 7 years warranty

### Versions / options

- Planet MinE-S << 27 dB
- Planet MinE-S → FH < 27 dB, fire-retardant</p>
- Airlock doors
- Special versions on request

### Door types with Planet MinE-S



Double leaf doors → refer to chapter Accessories | Flush bolt, drilling

#### More functions







## **Technical specifications**

Profile material	aluminum, → 13 x 30 mm
Channel material	aluminum,→ 30 x 43 mm
Groove size	width 30,1 mm with depth 43,5 mm /    width 13,1 mm with depth 30,5 mm
Seal profile	high-grade silicone or high-grade self-extinguishing silicone
Seal height	up to <b>↓ 27 mm</b>
Sound absorption value	up to <b>◀€ 27 dB</b> at 7 mm space to the floor
Air passage	30 m³/h at an aeration length of 1050 mm and a pressure difference of 3,9 Pa
Lift height adjustment	on the release knob with an Allen key 3 mm
Lengths in stock	335, 460, 585, 710, 835, 960, 1085, 1210, 1335, 1460 mm
Special lengths	on request up to 2000 mm, sliding doors up to 1600 mm
Release	unilaterally on hinge side
Can be shortened	up to the maximum of 125 mm (335 mm only 115 mm)
Fastening	on the side with stainless steel angle brackets and screws
Frame protector plate	stainless, hammer fixed, 20 x 20 mm
Test approvals	on request







