

Electric strike 138.60- - - - - F91

Product description

Model with bipolar protective diode for access control systems. Monitoring contact as potential-free changeover contact, actuated by the latch bolt.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Compatible with current mortise locks
- Compatible with ProFix® 1 striking plates
- Optimized sliding ramp for a smooth interplay with latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

Handing	Universal
potential	24 V DC
Adjustable latch (FF, FaFix®)	Yes
Monitoring contact (RR)	Yes
Fail-unlocked	Yes
Bi-directional diode	Yes
Rated operating voltage tolerance range	± 10 %
Rated resistance	160 Ohm
Switching capacity - monitoring contact	24 V / 1 A
Current consumption 24 V DC	150 mA
Current consumption DC (stabilised)	104 mA
Break-in resistance	3750 N
Max. latch preload DC (stabilised)	30 N
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-15 °C to +40 °C
Installation position	Vertical and horizontal
Load cycles for in-plant test	250000
Suitable for fire doors	No

Article number	138.60-----F91
----------------	----------------

