

Profile- half cylinder .532

Product description

- Brass cylinder
- Standard finish, satin nickel-plated (OF=MV)
- Number of pin tumblers and basic cylinder length (L=) depends on respective system
- Drilling protection (AB=), locking wave (SW=), additional lateral scanning, security card depending on profile (PR=)
- VdS class, DIN class, depending on profile (PR=)
- Spherical / Tapered cylinder core head with reinforced key guide
- Core pins made of special wear-resistant bronze
- Cam consisting of break and corrosion-resistant nickel silver profile or sinter metal, depending on system
- Standard cam position 90° left - 8x45° reversible (SST=8x45°)

Scope of delivery

- 1 profile half-cylinder
- 3 nickel silver keys
- 1 cylinder fixing screw M5 x 85 mm

Ordering Information

- Former BAB cylinder types .45 / .46 are available as variants P032/P632/P532, VAR2=2MM / VAR2=3B
- Attention: VAR=1901229+3+2MAL M4 is offered. This variant offers a second backside fixing thread M4.
- Without rear fixing hole M4 for P032 / P532 / 8532 / P632

Suitable ASSA ABLOY products

- Maintenance spray 8511
- Lockable window handle 9M10,AUS=PHZ VOR
- Door handle chain 9M34,AUS=PHZ VOR
- Mini safe 9M37,AUS=PZ VOR
- Mini safe 9M38,AUS=PZ VOR
- Mini safe 9M39,AUS=PZ VOR
- Mini safe 9M40,AUS=PZ VOR
- Escutcheon with rain protection cover 1255

