

Locking lever cylinder .320,AUS=1/.30

30 mm diameter, laterally flattened to 22 mm

Overview of Advantages

- The locking direction of the locking lever can be given when ordering; the locking direction can however be easily changed by changing the position of the stop screw

Product description

- Brass cylinder
- Standard finish, matt chrome-plated (OF=MC)
- Number of pin tumblers dependent on system
- Drilling protection (AB=), locking wave (SW=), additional lateral scanning (not possible for P030, P530 and P630), security card depending on profile (PR=)
- Spherical / Tapered cylinder core head with reinforced key guide
- Core pins made of special wear-resistant bronze
- Locking path and locking lever path 90° left or right
- Key withdrawal when locking lever is closed
- Fixing with M30x1.5 housing nut
- Standard locking lever (SLHB=1645009)

Scope of delivery

- 1 locking lever cylinder
- 2 nickel silver keys
- 1 housing nut M30 x 1.5 x 4
- 1 core nut, M10 x 0,75 x 3

Ordering Information

- The former BAB articles P030, P530 and P630 are available with the old article numbers
- Please include the desired locking path (SST=) in your order.

Suitable ASSA ABLOY products

- Maintenance spray 8511
- Escutcheon with rain protection cover 1254,AUS=1

