Bathroom lock N1001



Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 17 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Closed lock case
- Latch DIN left/right reversible without tools
- {DE weber}: Verschraubungsmöglichkeit für Beschläge durch das Schloss
- Stainless steel faceplate
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Product description

- OneSystem bathroom lock N1001 for single-leaf standard doors, product-specific environmental product declaration (EPD) in accordance with EN 15804 with article-specific Parameters.

Technical data

Bolt throw	20 mm
Material faceplate	Stainless steel
Handle follower	8 mm
Backset	55, 60, 65, 80, 100 mm
Distance	72 mm (vorgerichtet für Euro-Profilzylinder), 74 mm (vorgerichtet für Schweizer Rundzylinder)
Standards	EN 12209

Variants that can be ordered

Order number	Front plate	Face plate length	Distance
N10010008B*000L	R3 x 20 mm	235 mm	78 mm
N10010008B*000K	R3 x 24 mm	235 mm	78 mm
N10011008B*000L	R3 x 20 mm	235 mm	78 mm
N10011008B*000K	R3 x 24 mm	235 mm	78 mm
N10012008B*000M	R3 x 20 mm	235 mm	78 mm
N10013008B*000M	R3 x 20 mm	235 mm	78 mm