

## Deadbolt lock N1003

### Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 17 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Closed lock case
- Latch DIN left/right reversible without tools
- {DE weber}: Verschraubungsmöglichkeit für Beschläge durch das Schloss
- Stainless steel faceplate
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

### Product description

- OneSystem deadbolt lock N1003 for single-leaf standard doors, product-specific environmental product declaration (EPD) in accordance with EN 15804 with article-specific Parameters.

### Technical data

Bolt throw	20 mm
Material faceplate	Stainless steel
Handle follower	8 mm
Backset	55, 60, 65, 80, 100 mm
Distance	72 mm (vorgerichtet für Euro-Profilzylinder), 74 mm (vorgerichtet für Schweizer Rundzylinder)
Standards	EN 12209

### Variants that can be ordered

Order number	Front plate	Face plate length	Distance
N1003000XX*001B	R3 x 20 mm	185 mm	72 mm (vorgerichtet für Euro-Profilzylinder), 74 mm (vorgerichtet für Schweizer Rundzylinder)
N1003000XX*001A	R3 x 24 mm	185 mm	72 mm (vorgerichtet für Euro-Profilzylinder), 74 mm (vorgerichtet für Schweizer Rundzylinder)
N1003200XX*001E	R3 x 20 mm	185 mm	72 mm (vorgerichtet für Euro-Profilzylinder), 74 mm (vorgerichtet für Schweizer Rundzylinder)
N1003300XX*001E	R3 x 20 mm	185 mm	72 mm (vorgerichtet für Euro-Profilzylinder), 74 mm (vorgerichtet für Schweizer Rundzylinder)

