

Sash lock for fire doors N1050

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 17 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Closed lock case
- Latch DIN left/right reversible without tools
- {DE weber}: Verschraubungsmöglichkeit für Beschläge durch das Schloss
- Stainless steel faceplate
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Product description

- OneSystem sash lock N1050 according to EN 12209 for single-leaf standard doors/ approved for fire barriers according to EN 1634 / product-specific environmental product declaration (EPD) according to EN 15804 with article-specific parameters / tested for 1,000,000 cycles and 300 kg door weight

Technical data

Material faceplate	Stainless steel
Handle follower	8 mm
Backset	55, 60, 65, 80, 100 mm
Distance	72 mm (vorgerichtet für Euro-Profilzylinder), 74 mm (vorgerichtet für Schweizer Rundzylinder)
Standards	EN 12209
Bolt throw	20 mm

Variants that can be ordered

Order number	Front plate	Face plate length	Distance
N105000091*000L	R3 x 20 mm	235 mm	72 mm
N105000091*000K	R3 x 24 mm	235 mm	72 mm
N105010091*000L	R3 x 20 mm	235 mm	72 mm
N105010091*000K	R3 x 20 mm	235 mm	72 mm
N105020091*000M	R3 x 20 mm	235 mm	72 mm
N105030091*000M	R3 x 20 mm	235 mm	72 mm
N105000098*000L	R3 x 20 mm	235 mm	74 mm
N105000098*000K	R3 x 24 mm	235 mm	74 mm
N105010098*000L	R3 x 20 mm	235 mm	74 mm
N105010098*000K	R3 x 20 mm	235 mm	74 mm
N105020098*000M	R3 x 20 mm	235 mm	74 mm
N105030098*000M	R3 x 20 mm	235 mm	74 mm

